



JAPAN ENERJUMP Co., Ltd.

2-14-12 KW build.4F, Nihonbashi-kakigaracho, Chuo-ku, Tokyo 103-0014 JAPAN TEL: 03-6661-1807 FAX: 03-5651-3213 http://www.enerjump.co.jp/ E-mail: info@enerjump.co.jp





• POWER SERIES

NO DETAIL NO SUCCESS

















• POWER SERIES

Top Performance from POWER SERIES

POWER SERIES provides good service for both gas stations and drivers, which is the necessary dispenser for all.



Wide Range of Product Lineup

The Lineup of POWER SERIES meets various requirements of stations and customers. Choose the one that fits your needs.








Stylish Counter Area


Counter Area is assembled with Fiber Glass display panel that is designed with humanization and fashion. Customers can upgrade functions such as JEJ IC card system, printer, etc.



POWER SERIES

Enhanced Counter Display

The display with backlight LED is visible under any circumstances. Far more, the upgraded 8-digit readout can tackle with any currency in the world.





Handling Smoothly

With the upgradation of all hanging hardware, including nozzle, breakaway, hose and swivel, all actions of refueling can be done easily. The plastic type nozzle holder fits the nozzle perfectly and achieves high durability. The safety breakaway coupling cover prevents damage to dispenser in unpredicted situation.









Components with High Performance

We request every components and assembly process strictly and ensure every components can do their best for our customers.



Wide Variety of Options

We provide a wide range of options for our customers.
You can customize the dispenser so that it fits the best needs of you and your customers.








List of Functions


		List of Functions/Models				
Model Su	uction	PRGO1111	PRGO2121	PRGO2221	PRGO4241S	PRGO4241
Apperance		Control of the Contro				The state of the s
Fueling s P- Pump M M-Mete C- Coun N N- Nozz	er nter				N N N N N N N N N N N N N N N N N N N	
Fiber glass	s display panel	0		0		0
Moniter		\triangle	\triangle	\triangle	\triangle	\triangle
Pos prese	t		\triangle	\triangle	\triangle	\triangle
Keypad w	rith display	0	0	0		0
Hose 13ft	t (Hard)	0	0	0	0	0
Hose hanger		\triangle	\triangle	\triangle	\triangle	\triangle
	Auto-stop nozzle			0		
Nozzle	High speed nozzle	\triangle	\triangle	\triangle	\triangle	\triangle
	Ultra-high speed		\triangle	\triangle	\triangle	\triangle
Nozzle	Al		0			0
holder	Plastic		\triangle	\triangle		\triangle
Swivel		\triangle	\triangle	\triangle	\triangle	\triangle
Safety breakaway coupling		0	0	0		
Safety breakaway coupling cover		\triangle	\triangle	\triangle	\triangle	\triangle
Sight glas	SS	\triangle	\triangle	\triangle	\triangle	\triangle
Emergency-stop button		0	0	0	0	0
Static electricity discharge pad		\triangle	\triangle	Δ	\triangle	\triangle
Bulit-in printer		\triangle	\triangle	\triangle	\triangle	\triangle
LED poste		\triangle	\triangle			
JEJ IC card		\triangle	\triangle	\triangle	\triangle	\triangle


Dimensions

PRGO1111





PRGO2121/PRGO2221







PRGO4241





PRGO4241S









Stop static



Electromagnetic







main indicator Keypad

Emergency-stop button

■ Main Specifications

		Suction Pump Type	Submersible Turbine Pump (STP)Type			
Flow Rate		Normal:50L/min	Depends on the on-site STP capacity			
		High:70L/min				
		Ultra-high:90L/min				
Pump		Internal silent gear pump with air separator Suction strainer,Flexible pipe				
		By-pass valve and Suction check value				
Florrible Dine		Flange type,1-1/2"threaded				
Flexible Pipe Maunal Drive Handle		Provided for maunal operation during power failure				
Motor Motor		Three-phase 380V 750W				
		(Optional)Single-phase 220-240V 750W				
Meter		4-piston positive displacement flowmeter with electionic adjust er				
Accuracy		±0.3%				
Accurac	Type	LCD				
		Black charactors on a blue field with bright LED back light				
	Character Color	(Optional)White/Yellow/Orange back light				
		Sale: 8 digits[0.01~999,999.99]				
Counter	Display	Liter:8 digits[0.01~999,999.99]				
		Unit Price:5 digits[0.01~999.99]				
	Electromagnetic Totalizer	8 digits				
	Electronic Totalizer	(Optional) 8 digits				
		Battery back-up				
	Other Funtions	(Optional) Self-diagnosis				
		(Optional) Over voltage protector				
Reset Device		Automatic reset				
Nozzle		Automatic nozzle,Spout outside diameter 21mm,25mm				
Hose		Black color hose,Oil resistance type,Inside diameter 16mm				
		(Optional)Red/Yellow/Green color hose				
Safty Breakaway Couping		Provided				
Wiring		(Optional)Cabtyre cable				
Emergency Stop Switch		Provided				
POS Interface		(Optional)				
Line Fuel Filter		(Optional)				
Anti Static Touch Pad		(Optional)				
Sight Glass		(Optional)				
Receipt Printer		(Optional)				
AD Display		(Optional)				
LED Message Board		(Optional)				
Ambient Temperature		-40 to+ 60 °C				
Noise		≤80dB (A)				
Inlet Vacuum		≥0.06MPa				

Note: The delivery speed of the pump may change due to the following conditions if it is used beyond JEJ's installation and operational instructions:

1) Size and length of hose
2) Size and type of nozzle/swivel
3) Type of oil product, suction conditions, and local piping conditions

4) With/without presets
Specifications are subject to change with or without prior notice.

POWER SERIES is assembled with the reliable and efficient components that add powerful benefit to your business.

We deliver 'Japan Quality Japan Standard' dispensers to you.



⚠ We reserve the right to change the specifications and designs for improvement without prior notice.